NITRO-KOMBISPACHTEL

Page: 1

Compilation date: 13.04.2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Product name: U&@ ^||•] a&@^|A ^ã• Product code: 112 340 8 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of substance / mixture: Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel. 1.3. Details of the supplier of the safety data sheet Company name: Simprop electronic Walter Claas GmbH & Co KG Ostheide 5 D - 33428 Harsewinkel Deutschland Tel: [49] 05247 604-0 Fax: [49] 05247 604-15 Email: info@simprop.de 1.4. Emergency telephone number Emergency tel: 030-30686790 Section 2: Hazards identification 2.1. Classification of the substance or mixture Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336 Most important adverse effects: Flammable liquid and vapour. May cause drowsiness or dizziness. 2.2. Label elements Label elements: Hazard statements: H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Precautionary statements: P102: Keep out of reach of children.

NITRO-KOMBISPACHTEL

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P243: Take precautionary measures against static discharge.
P280: Wear protective gloves/protective clothing/eye protection.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water/shower.
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370+378: In case of fire: Use alcohol-resistant foam to extinguish.
P403+235: Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

N-BUTYL ACETATE

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
2	204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	1-10%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Page: 2

NITRO-KOMBISPACHTEL

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eves.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

NITRO-KOMBISPACHTEL

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Coated steel.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m3	966 mg/m3	-	-

Respirable dust

XYLENE

UK	220 mg/m3	441 mg/m3	-	_
	v	v		

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
equipment are not a source of ignition.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid			
	Characteristic odour			
Odour:	Characteristic odour			
Solubility in water:	Not miscible			
Also soluble in:	Most organic solvents.			
Viscosity:	Viscous			
Boiling point/range°C:	127	Melting point/range°C:	n.v.	
Flammability limits %: lower:	1,2	upper:	7,5	
Flash point°C:	32	Part.coeff. n-octanol/water:	n.v.	
Autoflammability°C:	370			[cont]

Page: 4

NITRO-KOMBISPACHTEL

Page: 5

Vapour pressure: 96,8 mbar

Relative density: 1,507 g/cm3

VOC g/l: 470

pH: n.a.

voc g/i.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

NITRO-KOMBISPACHTEL

 Page: 6

 Ingestion:
 There may be soreness and redness of the mouth and throat.

 Inhalation:
 There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

 Delayed / immediate effects:
 Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Waste code number:
 08 04 09

 Disposal of packaging:
 Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

NITRO-KOMBISPACHTEL

Page: 7

Marine pollutant: No

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	453/2010.		
	* indicates text in the SDS which has changed since the last revision.		
Phrases used in s.2 and s.3:	UH066: Repeated exposure may cause skin dryness or cracking.		
	H226: Flammable liquid and vapour.		
	H312: Harmful in contact with skin.		
	H315: Causes skin irritation.		
	H332: Harmful if inhaled.		
	H336: May cause drowsiness or dizziness.		
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any		
	damage resulting from handling or from contact with the above product.		